

# PRODUCT TECHNICAL STATEMENT

## DriStud Joining Tape

### Hand Tearable, Highly Adhesive Joining Tape

DriStud Joining Tape is a hand tearable joining tape, coated with a highly aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapour seal on all interior and exterior sheathing materials. DriStud Joining Tape exceeds most building code requirements and can be used for new construction as well as repair on all vapour barrier materials and vapour permeable wall and roof underlays. It is the highest performing, highest value product on the market, and it is available in white at 48mm wide width.

### PRODUCT CONSTRUCTION

Oriented polyester and acrylic adhesive

### FEATURES & BENEFITS:

- High performance tape installs and performs well over a wide temperature range.
- Excellent vapour barrier tape on polymer film
- Performs well as a joining tape on extruded foam products such as styrofoam.
- Applies to most of the wall and roof underlays. We guarantee performance on all the DriStud wall and roof underlays and Tyvek.

	Properties	Test Method	DriStud Joining Tape
1	Product Thickness	PSTC-133	0.087mm
2	Roll Size		48mm x 50m
3	Peel Adhesion- to stainless steel	PSTC-101	15.9N/25mm
4	Peel Adhesion- to polyethylene	PSTC-101	5.6N/25mm
5	Peel Adhesion- Tyvek	PSTC-101	8.8N/25mm
6	Shear Adhesion	PSTC-107	>24 hrs @ 15.2 kPa
7	Tensile Strength	PSTC-131	90.4N/25mm
8	Elongation	PSTC-131	130%
9	WVTR	ASTM E96	0.061 perms
10	Service Temperature		-40 to 85 °C

### WARRANTY

Please refer to DriSpace website [www.drinspace.co.nz](http://www.drinspace.co.nz) for more information on the warranty conditions.

For further information please visit  
[www.drinspace.co.nz](http://www.drinspace.co.nz) or call **0800 DRISTUD**  
**(374 7883)**.